Dr. Trampoline Repair Kit

The Dr. Trampoline jumping surface repair system will make all other time consuming repair methods obsolete. No need for a sewn on patch.

Holes about the size of a golf ball can be easily repaired by using this system.

Holes can be easily repaired without taking the jumping surface off the trampoline.





Dr. T. Kit Instructions:

Surface must be clean and dry before applying Dr. T. adhesive fabric.

- 1. The Dr. T. repair adhesive fabric should be applied to both the top and the bottom of the jumping surface. Cut the repair fabric into a patch larger than the hole to be repaired.
- 2. The Dr. T repair adhesive fabric should cover the hole or abrasion by at least 1-2" on all sides. Example: $2.5" \times 2.5"$ rounded off piece of the trampoline repair tape should be applied over a 1" hole.
- 3. The Dr. T repair adhesive fabric should be pressed firmly to the jumping surface with a rounded object (Example: the rounded bottom side of a spoon will work very well.)
 - This pressing motion will help to work the trampoline repair fabric adhesive into the trampoline fabric.
- 4. Heat will also help the Dr. T. repair fabric adhesive bond to the jumping surface. The heat from a hair dryer will warm the trampoline repair fabric to help the bonding process. Note: Be careful not to use too much heat as you could melt the trampoline fabric. Just use enough heat to warm the trampoline repair fabric slightly.

No warranty is expressed or implied. While this method of repairing holes has proven to be very effective with small holes, should the hole enlarge the jumping surface might have to be replaced, also if the jumping surface is very old replacing the jumping surface would be considered to be a better solution.